

Adjustable Steel Trench Struts

Specifications

- SCP offer an Adjustable Steel Trench Strut which features clawed end plates to support and grip the trench lining.
- All Adjustable Steel Trench Struts are thread rolled so there is no cutting away of material or loss of strength.
- Adjustable Steel Trench Struts are available in sizes No. 0 to No. 3.
- All SCP Trench Struts are manufactured in accordance with our ISO 9001:2000 quality system accreditation.

PRODUCT CODE	DESCRIPTION	LENGTH (m)		WEIGHT (kgs)
		Closed	Open	
9-280-HDI-00	Standard No. 0 Strut	0.32	0.47	4.0
9-280-HDI-01	Standard No. 1 Strut	0.49	0.73	5.8
9-280-HDI-02	Standard No. 2 Strut	0.69	1.09	7.7
9-280-HDI-03	Standard No. 3 Strut	1.03	1.73	11.0

Struts are fully tested in house on our own equipment.



Technical Information

- All props are manufactured to BS4074:2000.
- Sizes 1, 2, 3 supplied with captive inners.
- Safe working load: 3 tonnes, any size, any extension.
- Finished in one coat air drying.

High specification products designed to last...

1 Station Court, Girton Road, Cannock, Staffordshire WS11 0EJ
Tel: 01543 467 800 | Fax: 01543 467 993 | Email: acp@scpburton.co.uk

