U-Heads

Specifications

SCP offer two types of U-Head:

- **Fixed**
- **Adjustable**

U-Heads are designed to be used in conjunction with Adjustable Steel Props or System Scaffolding. The main function of a U-Head is to hold timber beams securely in place.

The Fixed U-Head comes complete with a 75mm spigot, which slots directly into an Adjustable Steel Prop or System Scaffold 16mm dia spigot.

For further adjustment the Adjustable U-Head can be used. It offers 500m of rolled threaded tube that can be adjusted by a double handle collar.

All SCP U-Heads are manufactured in accordance with ISO 9001:2000 quality system accreditation.

PRODUCT CODE	DESCRIPTION	MEASUREMENT			WEIGHT (kgs)
		Gap	Width	Height	
8-22-U/HEAD-F-4	4" (100mm) Fixed U-Head c/w 75mm long x 16mm diameter Spigot.	120	100	100	2.21
8-22-U/HEAD-F-6	6" (150mm) Fixed U-Head c/w Spigot	170	150	100	3.23
8-22-U/HEAD-F-8	8" (1200mm) Fixed U-Head c/w Spigot	220	150	100	4.25
8-22-U/HEAD-A-4	4" (100mm) Adjustable U-Head 38.1 x 4.88 x 650mm O/A 500mm T/L. c/w Double Handled Collar	120	100	100	4.70
8-22-U/HEAD-A-6	6" (150mm) Adjustable U-Head	170	150	100	5.75
8-22-U/HEAD-A-8	8" (200mm) Adjustable U-Head	220	150	100	6.80

Technical Information

- Safe working load: 4000kg (concentric loading).
- Adjustable U-Head Thread: TPI Acme BS4360/50C.
- U-Heads are independently tested and comply with Metal Scaffolding Standards BS1139 and EN74.

High specification products designed to last...

1 Station Court, Girton Road, Cannock, Staffordshire WS11 0EJ
Tel: 01543 467 800 | Fax: 01543 467 993 | Email: acp@scpburton.co.uk